ELOSTO 5 | 25

Electric Oscillating Tool



The ELOSTO 5 | 25 is a universal cutting tool for processing many different materials. It is always used when it is no longer possible to process materials with a drag knife.

ELOSTO is ideal for cutting soft and moderately dense materials. High processing speeds and very efficient processing are possible due to the very high stroke frequency.

ELOSTO is available with a 0.5 mm or 2.5 mm stroke depending on the application. A wide range of pointed or flat oscillating blades $\frac{1}{2}$

from the Zünd range of accessories can be used with the ELOSTO tool to accommodate specific material requirements and contour cuts. Flat-tipped knives are better suited for medium-density or fibrous materials and contour cuts with wide radii. The wide cutting area enables very high processing speeds.


Pointed knives are best for cutting out fine detail and precise, tight curves.











Benefits at a glance

ELOSTO enables very high cutting speeds

Robust construction designed for long-term use in industrial applications

Wide range of suitable flat and pointed knives available on MyZund

Best used for processing soft and medium-density materials.

Details

Two tool versions: 0.5 mm | 2.5 mm knife stroke

ELOSTO 5 oscillation frequency: 300 Hertz (18,000 rpm) ELOSTO 25 oscillation frequency: 250 Hertz (15,000 rpm)

Powerful electric drive with air cooling

ELOSTO 5 is suitable for use with 0.63 mm wide oscillating blades and the ELOSTO 25 with 1.5 mm wide knives.

An optional knife holder is available in the other size.

Air consumption: Max. 74 Nl/min

Operating pressure: 0.6 MPa

Compatible with Q-Line

